

6" x 3" x 1/4" I-Beam

ALLOWABLE UNIFORM LOADS (lbs./ft. / *N/m*.) Laterally Supported

 $A_w = 1.375 \text{ in.}^2 / 887.1 \text{mm.}^2$ $I = 15.87 \text{ in.}^4 / 7071772 \text{mm.}^4$ Wt. = 2.20 lbs./ft. / 3.27kg/m. S = 5.29 in.³ / 92751mm.³

SPAN	NO LATERAL	LATERALLY SUPPORTED						
FT/m	SUPPORT	MAXIMUM		DEFLECTION				
	MAX. LOAD	LOAD		L/100	L/150	L/180	L/240	L/360
5/1.52	364/5307	823/12008	F_{v}	/	/	759/ <i>11083</i>	569/8304	379/5525
6/1.83	184/ <i>2689</i>	685/ <i>10001</i>	F_{v}	/	576/8400	479/ <i>6995</i>	359/5238	239/ <i>3481</i>
7/2.13	104/ <i>1524</i>	587/ <i>8568</i>	F_{v}	576/8403	383/5591	319/ <i>4654</i>	239/3483	158/ <i>2311</i>
8/2.44	64/ <i>936</i>	513/7493	$F_{ m v}$	400/5844	266/3885	221/3232	166/ <i>2416</i>	110/ <i>1600</i>
9/2.74	42/610	433/6321	F_{v}	289/ <i>4211</i>	192/ <i>2796</i>	159/2325	119/ <i>1736</i>	79/ <i>1146</i>
10/3.05	28/415	350/ <i>5114</i>	F_b	214/3124	142/2072	118/ <i>1721</i>	88/1283	58/ <i>845</i>
11/3.35	20/292	289/ <i>4221</i>	F_b	163/2376	108/ <i>1573</i>	89/ <i>1306</i>	67/ <i>971</i>	44/637
12/3.66	14/ <i>210</i>	243/3542	F_b	126/ <i>1845</i>	84/ <i>1219</i>	69/ <i>1011</i>	51/ <i>750</i>	34/ <i>489</i>
13/3.96	11/ <i>154</i>	206/3013	F_b	100/ <i>1458</i>	66/ <i>961</i>	55/796	40/589	26/382
14/4.27	8/114	178/2594	F_b	80/1170	53/769	44/636	32/469	21/302
15/4.57	6/84	155/2255	F_b	65/ <i>951</i>	43/623	35/ <i>514</i>	26/377	17/ <i>241</i>

The part weight has been deducted in the above table.


English/ *Metric*


This item is stocked in 20-foot lengths.

Other lengths available in mill run quantities.

The mill run on this item is 800 feet.

Orders for less than mill run quantities will be subject to set-up charges as well as premium per foot cost.





Cooling Tower Depot | Corporate Circle | Golden, CO 80401 | Toll Free 877.243.3945 | Phone: 720.746.1234 | Fax: 720.746.1110